

Suspended platform EUROPA 2000 – CB 2-20

max. load each platform 140 kg/m
platform with two C-frames

Length (m)	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	
Variations (m)	1x2	1x3	2x2	1x3+ 1x2	2x3 or 3x2	1x3+ 2x2	4x2 or 2x3+ 1x2	3x3	2x3+ 2x2	3x3+ 1x2	4x3 or 2x3+ 3x2	3x3+ 2x2	4x3+ 1x2	5x3 or 3x3+ 3x2	4x3+ 2x2	5x3+ 1x2	6x3	5x3+ 2x2	6x3+ 1x2 or 4x3+ 4x2	
Type	CB2	CB3	CB4	CB5	CB6	CB7	CB8	CB9	CB10	CB11	CB12	CB13	CB14	CB15	CB16	CB17	CB18	CB19	CB20	
Dead weight	180	290	320	340	370	390	420	440	470	490	520	540	570	590	620	640	670	690	720	
Useful load hoist 500 kg	280	420	560	660	630	610	580	560	530	510	480	460	430	410	380	360	330	310	280	
Useful load hoist 800 kg	280	420	560	700	840	980	1120	1160	1130	1110	1080	1060	1030	700	700	700	700	700	700	
max. platform projection	max. 0,5 m from C-frame				max. 1,5 m from C-frame				max. 2,5 m from C-frame											

maximal distance between C-frames = 15 m

Suspended platform type EUROPA 2000 – K 2-15

platform with two stirrups (no platform projection)

Length (m)	2	3	4	5	6	7	8	9	10	11	12	13	14	15
Variations (m)	1x2	1x3	2x2	1x3+1x2	2x3 or 3x2	1x3+2x2	2x3+1x2 or 4x2	3x3	2x3+ 2x2	3x3+1x2	4x3 or 2x3+3x2	3x3+2x2	4x3+1x2	5x3
Type	K2	K3	K4	K5	K6	K7	K8	K9	K10	K11	K12	K13	K14	K15
Dead weight	200	220	250	270	300	320	350	370	400	420	450	470	500	520
Useful load hoist 500 kg	280	420	560	700	700	680	650	630	600	580	550	530	500	480
Useful load hoist 800 kg	280	420	560	700	840	980	1120	1180	1150	1130	1100	1080	1050	700

maximal distance between stirrups = 15 m

Suspended platform type EUROPA 2000 double deck platform – DCB 3-16

platform with two C-frames

Length (m)	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
Variations (m)	2x3	4x2	2x3+ 2x2	4x3 6x2	2x3+ 4x2	4x3+ 2x2	6x3	4x3+ 4x2	6x3+2x2	8x3 or 4x3+ 6x2	6x3+ 4x2	6x3+ 2x2	10x3	8x3+ 4x2	
Type	DCB3	DCB4	DCB5	DCB6	DCB7	DCB8	DCB9	DCB10	DCB11	DCB12	DCB13	DCB14	DCB15	DCB16	
Dead weight	450	500	550	600	650	700	750	800	850	900	950	1000	1050	1100	
Useful load hoist 500 kg	550	500	450	400	350	300	250	200							
Useful load hoist 800 kg	840	1100	1050	1000	950	900	850	800	750	700	650	600	550	500	
max. platform projection	max. 0,5 m from C-frame		max. 1,5 m from C-frame				max. 2,0 m from C-frame								

maximal distance between C-frames = 12 m

Suspended platform type EUROPA 2000 double deck platform – DK 2-12

platform with two stirrups (no platform projection)

Length (m)	2	3	4	5	6	7	8	9	10	11	12
Variations (m)	2x2	2x3	4x2	2x3+2x2	4x3 or 6x2	2x3+4x2	4x3+ 2x2	6x3	4x3+4x2	6x3+2x2	8x3 or 4x3+6x2
Type	DK2	DK3	DK4	DK5	DK6	DK7	DK8	DK9	DK10	DK11	DK12
Dead weight	300	350	400	450	500	550	600	650	700	750	800
Useful load hoist 500 kg	560	650	600	550	500	450	400	350	300	250	200
Useful load hoist 800 kg	560	840	1120	1130	1080	1030	1000	950	900	850	800

maximal distance between stirrups = 12 m